


600 DES/DX CR


Energy Efficient Specialty Dehumidification
Advanced Humidity Control

The 600 **DES/DX CR** is a modified version of NovelAire's DES/DX CR product line that provides for efficient operation over a wide range of operating conditions combined with a compact design to allow for significant flexibility with respect to installation. The DES/DX CR is a hybrid dehumidifier that integrates both refrigerant-based and desiccant dehumidification to achieve a synergistic effect and provide below freezing evaporator temperature. The single-path design avoids the need for a separate regeneration air stream. The 600 DES/DX CR can be used as a substitute for high temperature gas or electric regenerated units that are expensive to operate.



HOW IT WORKS

The first-pass through the desiccant wheel serves to concentrate moisture content in the air stream. Pre-heating with waste condenser amplifies moisture removal from the desiccant wheel. Moisture is rejected by the evaporator coil and further dehumidification occurs during the second-pass through the desiccant wheel. Additional condenser heat is rejected downstream from the wheel prior to discharge to the space.



FEATURES & BENEFITS

- Energy savings for low temps, low dewpoints
- Avoids expensive hi-temp gas / electric regen
- Sub-freezing dewpoint without regen stream
- Improved IAQ with independent %rh control
- Low-profile cabinet to suspend in drop-ceiling
- Improve material life; eliminate standing water
- NovelAire proprietary high performance desiccant wheel
- ETL listed, industrial-grade construction




APPLICATIONS

- Library and archives
- Water treatment facilities
- Cold storage, food preservation
- Museums, artifact storage
- Grocery store cold aisle
- Military equipment and munition storage
- School and university – laboratory, classroom



SPECIFICATIONS

Size:	42.3" W x 58.3" L x 17.8" H
Weight:	395lbs.
Electrical:	208-230V / 1Ph / 60Hz / 19.1FLA
Compressor:	2 ton; R410-A
Process Flow:	680 cfm
Fan:	1.5hp; 0.6" ESP
Capacity:	13.8lb/h (80F / 60% rh)
Certification	ETL Listed



NOVELAIRE TECHNOLOGIES
Creating the Great Indoors

10132 Mammoth Drive, Baton Rouge, LA 70814-4420
tel. 800-762-1320 / 225-924-0427 fax. 225-930-0340
www.novelaire.com



The information contained in this brochure is believed to be accurate by NovelAire Technologies, but is not warranted. Specifications subject to change without notice. Consult factory for special applications.

600DDXCR-R124745